

JFW

PTO/SB/21 (09-06)
Approved for use through 03/31/2007. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMITTAL FORM (to be used for all correspondence after initial filing)	Application Number	10/595,618
	Filing Date	May 1, 2006
	First Named Inventor	Durand et al.
	Art Unit	Unknown
	Examiner Name	Unknown
Total Number of Pages in This Submission	Attorney Docket Number	117180-009

ENCLOSURES (Check all that apply)		
<input type="checkbox"/> Fee Transmittal Form <input type="checkbox"/> Fee Attached <input type="checkbox"/> Amendment/Reply <input checked="" type="checkbox"/> After Final <input type="checkbox"/> Affidavits/declaration(s) <input type="checkbox"/> Extension of Time Request <input type="checkbox"/> Express Abandonment Request <input type="checkbox"/> Information Disclosure Statement <input checked="" type="checkbox"/> Certified Copy of Priority Document(s) <input type="checkbox"/> Reply to Missing Parts/ Incomplete Application <input type="checkbox"/> Reply to Missing Parts under 37 CFR 1.52 or 1.53	<input type="checkbox"/> Drawing(s) <input type="checkbox"/> Licensing-related Papers <input type="checkbox"/> Petition <input type="checkbox"/> Petition to Convert to a Provisional Application <input type="checkbox"/> Power of Attorney, Revocation Change of Correspondence Address <input type="checkbox"/> Terminal Disclaimer <input type="checkbox"/> Request for Refund <input type="checkbox"/> CD, Number of CD(s) _____ <input type="checkbox"/> Landscape Table on CD	<input type="checkbox"/> After Allowance Communication to TC <input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences <input type="checkbox"/> Appeal Communication to TC (Appeal Notice, Brief, Reply Brief) <input type="checkbox"/> Proprietary Information <input type="checkbox"/> Status Letter <input type="checkbox"/> Other Enclosure(s) (please identify below):
Remarks Certified Copy of EP 03024855.3 Return Receipt Postcard		


SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT			
Firm Name	Bell, Boyd & Lloyd LLC		
Signature			
Printed name	Robert M. Barrett		
Date	November 13, 2006	Reg. No.	30,142

CERTIFICATE OF TRANSMISSION/MAILING			
I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below:			
Signature			
Typed or printed name	Heather Foster	Date	November 13, 2006

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

THIS PAGE BLANK (USPTO)



Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

TRANSMITTAL FORM

(to be used for all correspondence after initial filing)

Total Number of Pages in This Submission

Application Number	10/595,618
Filing Date	May 1, 2006
First Named Inventor	Durand et al.
Art Unit	Unknown
Examiner Name	Unknown
Attorney Docket Number	117180-009

ENCLOSURES (Check all that apply)

- | | | |
|---|--|---|
| <input type="checkbox"/> Fee Transmittal Form
<input type="checkbox"/> Fee Attached
<input type="checkbox"/> Amendment/Reply
<input type="checkbox"/> After Final
<input type="checkbox"/> Affidavits/declaration(s)
<input type="checkbox"/> Extension of Time Request
<input type="checkbox"/> Express Abandonment Request
<input type="checkbox"/> Information Disclosure Statement
<input checked="" type="checkbox"/> Certified Copy of Priority Document(s)
<input type="checkbox"/> Reply to Missing Parts/
Incomplete Application
<input type="checkbox"/> Reply to Missing Parts
under 37 CFR 1.52 or 1.53 | <input type="checkbox"/> Drawing(s)
<input type="checkbox"/> Licensing-related Papers
<input type="checkbox"/> Petition
<input type="checkbox"/> Petition to Convert to a
Provisional Application
<input type="checkbox"/> Power of Attorney, Revocation
Change of Correspondence Address
<input type="checkbox"/> Terminal Disclaimer
<input type="checkbox"/> Request for Refund
<input type="checkbox"/> CD, Number of CD(s) _____
<input type="checkbox"/> Landscape Table on CD | <input type="checkbox"/> After Allowance Communication to TC
<input type="checkbox"/> Appeal Communication to Board
of Appeals and Interferences
<input type="checkbox"/> Appeal Communication to TC
(Appeal Notice, Brief, Reply Brief)
<input type="checkbox"/> Proprietary Information
<input type="checkbox"/> Status Letter
<input type="checkbox"/> Other Enclosure(s) (please identify
below): |
|---|--|---|
- Remarks
Certified Copy of EP 03024855.3
Return Receipt Postcard

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT

Firm Name	Bell, Boyd & Lloyd LLC		
Signature			
Printed name	Robert M. Barrett		
Date	November 13, 2006	Reg. No.	30,142

CERTIFICATE OF TRANSMISSION/MAILING

I hereby certify that this correspondence is being facsimile transmitted to the USPTO or deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below:

Signature			
Typed or printed name	Heather Foster	Date	November 13, 2006

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to 2 hours to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

THIS PAGE BLANK (USPTO)



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: Durand et al.
Appl. No.: 10/595,618
Filed: May 1, 2006
Conf. No.: 3622
Title: A CONTAINER FOR PRODUCT WITH LESS PACKAGING MATERIAL
Art Unit: Unknown
Examiner: Unknown
Docket No.: 117180-009

Mail Stop
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

SUBMISSION OF CERTIFIED COPY OF PRIORITY DOCUMENT

Applicants are respectfully enclosing the certified copy of the priority document for which priority is claimed for the above-identified application under 35 U.S.C. §119. Specifically, the document enclosed is:

<u>Document No.</u>	<u>Country</u>	<u>Date</u>
03024855.3	Europe	October 31, 2003

The Commissioner is hereby authorized to charge deposit account 02-1818 for any fees which are due and owing.

Respectfully submitted,

BELL, BOYD & LLOYD LLC

BY 

Robert M. Barrett
Reg. No. 30,142
Customer No.: 29157

Dated: November 13, 2006

THIS PAGE BLANK (USPTO)



✉ EPA/EPO/OEB
D-80298 München
☎ +49 89 2399-0
TX 523 656 epmu d
FAX +49 89 2399-4465

Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

Generaldirektion 2

Directorate General 2

Direction Générale 2

NESTEC S.A. IP DEPARTMENT-PATENTS
Attn. Rosina AMENDOLA NO 7630/GF
Avenue Nestlé 55
1800 VEVÉY - Switzerland

Datum/Date

21/04/06

Zeichen/Ref./Réf.

NO 7630/GF

Anmeldung Nr./Application No./Demande n°/Patent Nr./Patent No./Brevet n°.

03024855.3 1261 1527999

Anmelder/Applicant/Demandeur/Patentinhaber/Proprietor/Titulaire

Nestlé Waters Management & Technology

Übersendung von/Transmission of/Envoi de

Antrag vom/Request dated/Requête du 20/04/06

☐

Kopien bei Akteneinsicht nach Regel 94(3) EPÜ
Copies in the case of inspection of files pursuant to Rule 94(3) EPC
Copies en cas d'inspection publique selon la règle 94(3) CBE

☐

Beglaubigung
Certification
Certification

☒

2 Prioritätsbeleg(e)/priority document(s)/document(s) de priorité R. 94(4)

☐

Ausfertigung(en) der Patenturkunde nach Regel 54(2) EPÜ
Duplicate of the patent certificate pursuant to Rule 54(2) EPC
Duplicata du certificat de brevet, selon la Règle 54(2) CBE

☐

Auszug aus dem Register nach Regel 92(3) EPÜ
Extract from the register pursuant to Rule 92(3) EPC
Extrait du registre selon la Règle 92(3) CBE

☐

Auskunft aus den Akten nach Regel 95 EPÜ
Communication of information contained in the files pursuant to Rule 95 EPC
Communication d'informations contenues dans la dossier selon la Règle 95 CBE

☐

Akteneinsicht nach Regel 94(2) EPÜ
Inspection of files pursuant to Rule 94(2) EPC
Inspection publique selon la Règle 94(2) CBE

THIS

BLANK

THIS PAGE BLANK (USPTO)

PAGE 1 (USPTO)



**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

03024855.3

Der Präsident des Europäischen Patentamts;
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

R C van Dijk

THIS PAGE BLANK (USPTO)



Anmeldung Nr:
Application no.: 03024855.3
Demande no:

Anmeldetag:
Date of filing: 31.10.03
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Nestlé Waters Management & Technology
20, rue Rouget de Lisle
92130 Issy-les-Moulineaux
FRANCE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.
If no title is shown please refer to the description.
Si aucun titre n'est indiqué se référer à la description.)

A container for product with less packaging material

In Anspruch genommene Priorität(en) / Priority(ies) claimed /Priorité(s)
revendiquée(s)
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/
Classification internationale des brevets:

B65D/

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL
PT RO SE SI SK TR LI

THIS PAGE BLANK (USPTO)

- 1 -

A container for product with less packaging material.

5 The present invention relates to the field of the packaging of flowable products such as liquids or pasty products , particularly that of containers intended to contain beverages and more especially mineral water.

10 One topic in the packaging area, especially for water is to reduce the weight of the plastic material used, and more particularly to reduce the weight of the bottom of the container. By reducing the weight of the bottom, the first danger is that said bottom is less resistant because of the fact that the bottom is really the part of the container , which is the more submitted to
15 constraints, due to the contact of said bottom with the place where it is disposed. There are already some solutions to that problem, like the container with petaloid bottom : the FR Patent No. 2772720 concerns such a container, wherein the bottom is thinner. Although this
20 patent brings a solution for the bottom, it remains a container with a too high amount of plastic material for the volume of the product filled in said container.

25 The objective of the present invention is to have a container for a flowable product with a bottom allowing said container to stand and which for the same volume requires less plastic than a standard container while at the same time having comparable or higher mechanical properties.

30 The subject of the present invention is a container comprising a body formed by walls and a bottom having in his greater section a dimension d_1 and a neck with an internal diameter d_2 , said container being made from a
35 semi-crystalline PET , the body of said container comprising at its bottom at least three feet spaced from each other and being integral with said body, wherein for the body, the ratio weight of the walls on weight of the

- 2 -

bottom is comprised between 3 and 4 and wherein the ratio volume of the body of the container per gram of PET of the body is comprised between 80 and 120. The volume is given in ml.

5

Under bottom in the present description, we understand all the part of the body comprising the space of said body outside the feet, said feet being taken from their most external position.

10

Semi-crystalline PET means in the present specification a PET having a crystallinity comprised between 10 and 60 %. More preferably, the crystallinity is comprised between 20 and 40 %.

15

One specificity of the invention is that the container has feet at the bottom, which are integral with said body. The presence of three feet is a good solution, but for greater volume a presence of 4 or 5 feet is preferred. The geometry of said feet is not critical. Preferably, these feet have a spherical geometry. Concerning the bottom of the container, it has preferably a non flat form. The bottom has a convex form, like a semi-spherical form.

25

It is possible for the container of the invention, either to have a neck with a small height, like a couple of millimeters, or to have a neck with a greater height. In this case, the ratio height of the neck on the height of the body is comprised between 1:1 and 1:4. This allows for the consumer a better gripping of said container.

30

Preferably, the walls of the body have a thickness of less than 100 μm . The neck of the container has preferably a wall thickness comprised between 150 and 250 μm . Each foot of the bottom of the body has a thickness comprised between 50 and 150 μm .

35

- 3 -

In the container of the invention, the part of the bottom between the feet has a greater thickness of that of the walls, for example around 100-200 μm .

- 5 The present invention concerns further a packaging assembly comprising
- a container comprising a body formed by walls having in his greater section a dimension d_1 and a neck with an internal diameter d_2 , said container being made from a
- 10 semi-crystalline PET, the body of said container comprising at its bottom at least three feet spaced from each other and being integral with said body, wherein for the body, the ratio weight of the walls on weight of the bottom is comprised between 3 and 4 and wherein the ratio
- 15 volume of the body of the container per gram of PET of the body is comprised between 80 and 120,
- a product in the container and
 - closing means for closing off or distributing the product from the neck,
- 20 the filled container being substantially incompressible by hand when filled with the product.

This incompressibility applies for all types of products, even for a still product. In the present specification,

25 incompressible means that when squeezed the filled container only deforms very slightly and then will recover its original shape. In contrast, a standard bottle will buckle and deform.

30 According to a feature of the invention, the container comprises on its outside a printing made by pad printing. The advantage of this solution, is that it suppresses the need of having a paper stuck around the container.

35 The volume of the container used according to the invention can have all type of capacity, comprised between 5 cl and 20 l capacity. The container is intended to contain all type of product, like pasty, liquid, semi-

- 4 -

liquid, granular or powdered product. Under liquid product, we understand water or a still liquid beverage, particularly still mineral waters, carbonated water or a carbonated liquid beverage, particularly sparkling mineral water. Other types of liquid products are also possible, like chemical products, oil, essence, perfumes, pharmaceutical products. Under pasty products, we understand food and non food products, like mayonnaise, cosmetic compounds and others.

10

The means of closing are either a cap, or sealed membrane. The caps can be used for any diameter of opening of the neck. On the contrary, the sealed membranes are preferred with smaller diameter of the neck, for example in the area of 10 mm. In this case, the container can support high compressions, for example by the storage and by the transportation. For diameters of around 10 mm, the container can support an internal pressure of the order of 5 bar. It is also possible to close the container by sealing or welding the neck, wherein a cutting object or similar is provided for the opening.

As a preference, the container has an ovoid or substantially ovoid overall shape. This natural shape derived from an egg represents a structure whose resistance to vertical and/or transversal loads is optimized, thus making it possible, for a given volume and a given amount of material, to achieve mechanical properties which are equivalent to or even better than the cylindrical or roughly cylindrical shapes customarily encountered in this domain.

In another embodiment, the container according to the invention has a three dimensional shape convenient for gripping, a spherical, substantially spherical or cylindrical overall shape.

- 5 -

This is because the geometry with symmetry of revolution is particularly easy and therefore economical to manufacture and has the advantage of allowing the container to be filled with products which can emit
5 gaseous substances, such as carbonated beverages (sparkling waters, sodas, etc.) in particular, which are widely consumed worldwide these days. Such a shape is therefore particularly well suited to these liquids in that the release of carbon dioxide or other gas has a
10 tendency to deform the bodies of bottles which do not have symmetry of revolution, having a negative impact on their stability, grasp and ease of handling, appearance, etc.

15 In a preferred feature of the invention, the ratio d_2 on d_1 of the container is comprised between 1:3 and 1:10. According to a preferred embodiment of the packaging assembly, the ratio weight of the walls on weight of the bottom is comprised between 3.4 and 3.8. According to a
20 further preferred feature of the invention, the ratio volume of the body of the container per gram of PET of the body is comprised between 90 and 110.

According to another feature, the plastic used to form
25 the wall or walls is a semicrystalline plastic with a slow rate of crystallization, the glass transition temperature (T_g) of which is 70°C or higher and the cristallisation temperature T_c is around 140 °C. A slow rate of crystallization is to be understood as
30 meaning a rate which makes it possible to have an amorphous state by quick cooling.

Advantageously, the plastic used to form the wall or walls is chosen from the group formed by PET
35 (polyethylene terephthalate) and PEN (polyethylene naphthalate). It has been noted that the drawing of the PET has no negative influence on the water barrier properties of the obtained container and that also a

- 6 -

thickness of around 50 μm and less guarantees a good safety of the container itself and of the storage.

In order to guarantee both the flexibility needed for the aforementioned deformation and sufficient mechanical strength, the container according to the invention is further characterized in that the thickness of the wall or walls forming the body of the container is between 30 μm and 100 μm , preferably between 50 μm and 70 μm .

As already mentioned, small thicker areas or portions of walls may also be provided on the body of the said container, particularly in close proximity to the neck and/or the bottom, so as to reinforce these parts locally. Such reinforcements may in particular be useful to facilitate the filling of the said containers or to increase their stability during storage.

As a preference, the container is further characterized in that the body and the neck of the container are made as a single piece. This makes it possible to avoid any join or weld which may constitute a region of greater weakness.

Indeed, according to another feature, the container according to the invention is characterized in that, it has a high resistance to vertical and/or transverse loads allowing good resistance to transportation. For example, for a working volume of 5 litres, the amount of PET used to produce the said container is about 30 g. for resistance to a vertical load of about 65 kg. This represents a significant saving in plastic, the few 5-litre containers that are currently on the market requiring an amount of polymer which, for comparable mechanical strength, is over two times greater than the amount needed to manufacture a container according to the present invention. When containers of lower volumes are used, for example of the order of 33 cl, the quantity of plastic material is of the order of 3-4 g, in comparison with a bottle of the same volume, wherein the amount of plastic is of the order of at least 12 g. This type of

- 7 -

container supports a vertical loading of more than about 100 kg. That the container supports a vertical or transverse loading means that the weight given does not deteriorate the package integrity, that is does not lead
5 to a risk of breaking said container.

These simple shapes also allow the container according to the invention to be used as a refill or recharge for water coolers, for which a flat bottom is not necessary,
10 these refills generally being used by inserting the container, head (neck) downmost, into the accommodation device of the said water cooler. In addition, this type of surface geometry also makes it possible to increase the area of heat exchange between the said container and
15 the chilling device usually present in the said water coolers.

According to another alternative form, the container according to the invention is characterized in that the
20 neck is fitted with a closure and/or distribution means produced in the form of a distribution tap which can be operated with one hand.

Such distribution taps, which are known per se,
25 advantageously allow the distribution of the flowable product contained in the container to be regulated in a particularly convenient way, for example when this container is stored horizontally on the shelves of a refrigerator, the other hand holding the container into
30 which the said flowable product is to be transferred, for example with a view to consuming it.

Because of its flexible nature, the geometry of the container can also adapt more readily to that of the storage place, as opposed to the rigid cans currently
35 available which need to observe very specified dimensions in order to be able to be stored in restricted spaces such as the internal compartments of refrigerators. In addition, the space freed as a container according to the

- 8 -

invention is emptied can also be put to use for storing objects the size or shape of which can vary, which is not the case with rigid containers in which the volume of liquid removed is systematically replaced with air. In this type of container, the volume initially occupied remains so until the empty container is removed from the refrigerator.

Another subject of the present invention is the use of the container by way of large-capacity, at least 5-litre capacity, container intended to contain water or a still liquid beverage, particularly still mineral water.

Another subject of the present invention is the use of the container according to the invention by way of large-capacity, at least 5-litre capacity, container intended to contain carbonated water or a carbonated liquid beverage, particularly sparkling mineral water.

Of course, the containers of the present invention are not in any way limited to flat or sparkling mineral waters but can be intended to contain all sorts of flowable products, edible or inedible liquids of greater or lesser fluidity such as, for example, fruit juices, milk-based beverages, etc., and also sauces or condiments (ketchup, mustard, dressing, etc.) or non-food liquids (deionized water, cleaning products, detergents, etc.).

The packaging assembly according to the invention can also contain a functional component. The functional component is taken from the group consisting of a fibre, plant extract, fruit extracts, vitamins and flavors. The assembly is pasteurised or sterilised at a temperature in excess of 60 °C.

Finally, another subject of the present invention is a method for manufacturing a body of a container according to the invention, characterized in that the said body is obtained by stretch blow forming of a PET preform with high stretch index in comparison with the classical

- 9 -

stretching of a preform. The blow forming can be also a blow molding. Compared with the blowing of plastic bottles, wherein the blowing pressure is comprised between 30 and 40 bar, according to the process of the invention, it is sufficient to blow at a pressure of around 2 times less. This reduces the cost of the process and also of the machine which is used. Concerning the stretch index, it is depending of the volume of the final container. For example, in the case of a container having a volume of less than 100 cl, the stretch index is between 100 and 300 cm. In the case of a container having a volume of 500 to 1000 cl, the stretch index is comprised between 500 and 700 cm. In the case of container having volume of 2000 cl or more, the stretch index is around and more than 1000 cm.

The stretch index is defined as follows :

$$\text{Stretch index} = \frac{\text{internal volume of the stretched container}^*}{\text{internal volume of the preform before stretching}^*} \times \frac{1}{f}$$

$$f = \frac{\text{internal surface of the container}^*}{\text{internal volume of the stretched container}^*} \quad (\text{cm}^{-1})$$

* with the exclusion of the neck

In the embodiments of the containers according to the invention, for volumes of 33 cl, 1 liter, 5 l, 10 l and 20 l, the different ratios S2 on S1 are comprised between 1:4.5 and 1:15.

Because of the substantial incompressibility of the filled container of the invention, there is no need to have reinforcing structures. The consequence is that it is possible to have simple shapes, which have the advantage of providing transparency and purity. This is particularly important for the consumer in the case of a container for drinking water. Another advantage of this

- 10 -

container is that it can be emptied without air coming in and this reduces the risk of contamination or odours entering the product that may cause taste changes or degradation.

5

The measure of the crystallinity is made on a density column from Lloyd-Davenport, according to following procedure. The column is filled with a salted solution (calcium nitrate) having a density gradient. The column is calibrated with balls having known density between 1.335 and 1.455. Then small pieces of the container of the invention are immersed in the column and after a certain time, they stay at a certain height of the column corresponding to a certain density. The measures are made at 23 °C. The following correspondance table with ρ_c of 1.455 gives the cristallinity

Density (ρ in g/cm ³)	Crystallinity (%)
$\rho_c = 1.335$	$\rho_c = 1.335$
$\rho_c = 1.345$	$\rho_c = 1.345$
$\rho_c = 1.355$	$\rho_c = 1.355$
$\rho_c = 1.365$	$\rho_c = 1.365$
$\rho_c = 1.375$	$\rho_c = 1.375$
$\rho_c = 1.385$	$\rho_c = 1.385$
$\rho_c = 1.395$	$\rho_c = 1.395$
$\rho_c = 1.405$	$\rho_c = 1.405$
$\rho_c = 1.415$	$\rho_c = 1.415$
$\rho_c = 1.425$	$\rho_c = 1.425$
$\rho_c = 1.435$	$\rho_c = 1.435$
$\rho_c = 1.445$	$\rho_c = 1.445$
$\rho_c = 1.455$	$\rho_c = 1.455$
$\rho_c = 1.465$	$\rho_c = 1.465$
$\rho_c = 1.475$	$\rho_c = 1.475$
$\rho_c = 1.485$	$\rho_c = 1.485$
$\rho_c = 1.495$	$\rho_c = 1.495$
$\rho_c = 1.505$	$\rho_c = 1.505$
$\rho_c = 1.515$	$\rho_c = 1.515$

- 11 -

Other features and advantages of the invention will become apparent from the description which follows, given by way of example and with reference to the appended drawings in which:

5

Fig. 1 is a lateral perspective view of the container according to the invention,

10

Fig. 2 is another perspective view of the container of the invention, seen from the bottom and

Fig. 3 is a graph comparing the invention with the state of the art.

15

In the embodiment described and depicted on figures 1 and 2, the container for a flowable product, particularly for a beverage and, in particular, for mineral water, essentially consists of a body 1, formed by walls 2 and a bottom 3 and a neck 4. The body is made of a semi-

20

crystalline PET. The neck presents a screw 5 for receiving a cap (not shown). The bottom 3 presents three feet 6 integral with the body. The volume of the container is of 1000 ml. In this specific example the ratio weight of the walls on weight of the bottom is of

25

3.5 and the ratio volume of the body of the container per gram of PET is of 100. This means that for the volume of 1000 ml, there is 10 g of PET for the body (neck excluded). The thickness of the walls is around 70 μm .

30

The neck has a height which is minimised and said neck has a wall thickness of around 200 μm . In the area 7 of the feet, that means around the middle of said feet, the wall thickness is around 150 μm . The feet have a semi-spherical shape. Concerning now the limits of the wall and bottom for calculating the ratio weight of the walls on weight of the bottom, it is outside and inside of the circle 8 of figure 2.

35

- 12 -

Concerning now the graph of figure 3, the x axis represents the volume of the container in ml and the y axis represents the ratio volume of the container in ml per g of the plastic material of said container. The graph 1 shows a bottle used on the market for sparkling water. The graph 2 shows a bottle used on the market for still water and the graph 3 shows a container according to the invention. This graph shows very clearly one of the specificity of the invention, which is that less plastic material is needed for conditioning the same volume of product, Taking an example of the graph : according to the invention 1 g of plastic material is needed for 100 ml of product, whereas for products now on the market 1 g of plastic material is needed for only around 40 to 60 ml of product. That means that according to the invention, the need of plastic material is divided by 2.

- 13 -

Claims.

- 1) A container comprising a body formed by walls and a bottom having in his greater section a dimension d_1 and a neck with an internal diameter d_2 , said container being made from a semi-crystalline PET, the body of said container comprising at its bottom at least three feet spaced from each other and being integral with said body, wherein for the body, the ratio weight of the walls on weight of the bottom is comprised between 3 and 4 and wherein the ratio volume of the body of the container per gram of PET of the body is comprised between 80 and 120.
- 2) A container according to claim 1, wherein the walls of the body have a thickness of less than 100 μm .
- 3) A container according to any of claims 1 or 2, wherein the neck has a wall thickness comprised between 150 and 250 μm .
- 4) A container according to any of claims 1 to 3, wherein each foot has a wall thickness comprised between 50 and 150 μm .
- 5) A container according to any of claims 1 to 4, wherein the part of the bottom between the feet has a greater thickness of that of the walls.
- 6) A packaging assembly comprising
- a container comprising a body formed by walls having in his greater section a dimension d_1 and a neck with an internal diameter d_2 , said container being made from a semi-crystalline PET, the body of said container comprising at its bottom at least three feet spaced from each other and being integral with said body, wherein for the body, the ratio weight of the walls on weight of the bottom is comprised between 3 and 4 and wherein the ratio

- 14 -

- volume of the body of the container per gram of PET of the body is comprised between 80 and 120,
- a product in the container and
 - closing means for closing off or distributing the
- 5 product from the neck,
the filled container being substantially incompressible by hand when filled with the product.
- 10 7) A packaging assembly according to claim 6, wherein the product is taken from the group consisting of pasty, liquid, semi-liquid, granular or powdered product.
- 15 8) A packaging assembly according to any of claims 6 or 7, wherein said assembly has a high resistance to vertical and/or transverse loads allowing good resistance to transportation.
- 20 9) A packaging assembly according to claim 8, wherein said assembly supports a vertical and/or transverse loading of more than about 100 kg for a container having a weight of about 4 g.
- 25 10) A packaging assembly according to any of claims 4 to 9, wherein the body of the container has a form taken from the group consisting of a three dimensional shape convenient for gripping, an ovoid, spherical, elliptical or cylindrical shape.
- 30 11) A packaging assembly according to any of claims 4 to 10, wherein the wall thickness of the body, substantially in the middle of its body is comprised between 30 and 70 μm .
- 35 12) A packaging assembly according to any of claims 4 to 11, wherein the container comprises on its outside a printing made by pad printing.

- 15 -

- 13) A packaging assembly according to any of claims 4 to 12, wherein the ratio d_2 on d_1 is comprised between 1:3 and 1:10.
- 5 14) A packaging assembly according to any of claims 4 to 13, wherein the ratio height of the neck on the height of the body is comprised between 1:1 and 1:4.
- 10 15) A packaging assembly according to any of claims 4 to 14, the ratio weight of the walls on weight of the bottom is comprised between 3.4 and 3.8.
- 15 16) A packaging assembly according to any of claims 4 to 15, wherein the ratio volume of the body of the container per gram of PET of the body is comprised between 90 and 110.
- 20 17) A process for manufacturing the container according to any of claims 1 to 5, wherein said container is obtained by stretch blow forming of a PET preform with high stretch index in comparison with the classical stretching of a preform.


- 16 -

Abstract

A container for product with less packaging material.

- 5 The invention concerns a container comprising a body 1
formed by walls 2 and a bottom 3 having in his greater
section a dimension d_1 and a neck 4 with an internal
diameter d_2 , said container being made from a semi-
crystalline PET, the body of said container comprising
10 at its bottom at least three feet spaced from each other
and being integral with said body, wherein for the body,
the ratio weight of the walls on weight of the bottom is
comprised between 3 and 4 and wherein the ratio volume of
the body of the container per gram of PET of the body is
15 comprised between 80 and 120.

Figure 1.



BEST AVAILABLE COPY





FIG. 2

FIG. 3.



BEST AVAILABLE COPY

THIS PAGE BLANK CUSTO